



WALL CONSTRUCTION
 EXTERNAL WALLS TO HAVE 100mm FACING BRICKS, 100mm CAVITY TO BE FILLED WITH PART 1 OF 2002 BUILDING REGULATIONS USE 5 NUMBER STAINLESS STEEL WALL TIES PER 450mm VERTICALLY AND 900mm HORIZONTALLY TO BE FITTED TO THE EXISTING WALLS. THE EXISTING WALLS TO BE REINFORCED WITH 125mm THICK CONCRETE TO ACHIEVE A V VALUE OF 0.22W/M2K.

ROOF CONSTRUCTION
 THE ROOF TO BE REINFORCED WITH 125mm THICK CONCRETE TO ACHIEVE A V VALUE OF 0.22W/M2K. THE ROOF TO BE REINFORCED WITH 125mm THICK CONCRETE TO ACHIEVE A V VALUE OF 0.22W/M2K.

WATERPROOFING
 THE ROOF TO BE WATERPROOFED WITH 1.5mm THICK POLYURETHANE MEMBRANE TO BE FITTED TO THE EXISTING ROOF.

MECHANICAL SERVICES
 THE MECHANICAL SERVICES TO BE FITTED TO THE EXISTING SERVICES.

PLUMBING
 THE PLUMBING TO BE FITTED TO THE EXISTING PLUMBING.

ELECTRICAL
 THE ELECTRICAL TO BE FITTED TO THE EXISTING ELECTRICAL.

HEATING
 THE HEATING TO BE FITTED TO THE EXISTING HEATING.

VENTILATION
 THE VENTILATION TO BE FITTED TO THE EXISTING VENTILATION.

GLAZING
 THE GLAZING TO BE FITTED TO THE EXISTING GLAZING.

INSULATION
 THE INSULATION TO BE FITTED TO THE EXISTING INSULATION.

FINISHES
 THE FINISHES TO BE FITTED TO THE EXISTING FINISHES.

CONCRETE
 THE CONCRETE TO BE FITTED TO THE EXISTING CONCRETE.

BRICKWORK
 THE BRICKWORK TO BE FITTED TO THE EXISTING BRICKWORK.

PLASTER
 THE PLASTER TO BE FITTED TO THE EXISTING PLASTER.

PAINT
 THE PAINT TO BE FITTED TO THE EXISTING PAINT.

GLASS
 THE GLASS TO BE FITTED TO THE EXISTING GLASS.

STEEL
 THE STEEL TO BE FITTED TO THE EXISTING STEEL.

WOOD
 THE WOOD TO BE FITTED TO THE EXISTING WOOD.

STONE
 THE STONE TO BE FITTED TO THE EXISTING STONE.

OTHER
 THE OTHER TO BE FITTED TO THE EXISTING OTHER.

DESIGN & DRAWING
A.T.
 12 Goldcrest Walk | Thorne Hasley | Rothham | South Yorkshire | S61 2TS
 Tel: 01742 453116 | 017739 807280
 e-mail: alan@adesignanddrawing.com
 www.adesignanddrawing.com

REV.	MODIFICATIONS	DATE

Client Scheme
 Title
 Drawing No.
 Sheet No.